

(12)

EUROPEAN PATENT APPLICATION

(11) Application number: 89118069.7

(51) Int. Cl. 5: A61F 2/06

(22) Date of filing: 29.09.89

(20) Priority: 04.10.88 US 253115

(43) Date of publication of application:
25.04.90 Bulletin 90/17

(52) Designated Contracting States:
AT BE CH DE ES FR GB GR IT LI LU NL SE

(71) Applicant: EXPANDABLE GRAFTS
PARTNERSHIP a Texas General Partnership
2 Carriage Hill
San Antonio Texas 78257(US)


(72) Inventor: Schatz, Richard A.
6342 East Maverick Road
Paradise Valley Arizona 85253(US)

(74) Representative: Patentanwälte Grünecker,
Kinkeldey, Stockmair & Partner
Maximilianstrasse 58
D-8000 München 22(DE)

(54) Expandable Intraluminal graft.

(57) A plurality of expandable and deformable intraluminal vascular grafts are expanded within a blood vessel by an angioplasty balloon associated with a catheter to dilate and expand the lumen of a blood vessel. The grafts may be thin-walled tubular members (71) having a plurality of slots (82) disposed substantially parallel to the longitudinal axis of the tubular members (71), and adjacent grafts are flexibly connected by a single connector member disposed substantially parallel to the longitudinal axis of the tubular members.

Fig. 1B



EP 0 364 787 A1

any surgical procedures could be performed.

Additional disadvantages associated with balloon dilation of elastic vascular stenoses is that many fail because of elastic recoil of the stenotic lesion. This usually occurs due to a high fibrocollagenous content in the lesion and is sometimes due to certain mechanical characteristics of the area to be dilated. Thus, although the body passageway may initially be successfully expanded by a balloon dilation procedure, subsequent, early restenosis can occur due to the recoil of the body passageway wall which decreases the size of the previously expanded lumen of the body passageway. For example, stenoses of the renal artery at the ostium are known to be refractory to balloon dilation because the dilating forces are applied to the aortic wall rather than to the renal artery itself. Vascular stenoses caused by neointimal fibrosis, such as those seen in dialysis-access fistulas, have proved to be difficult to dilate, requiring high dilating pressures and larger balloon diameters. Similar difficulties have been observed in angioplasties of graft-artery anastomotic strictures and postendarterectomy recurrent stenoses. Percutaneous angioplasty of Takayasu arteritis and neurofibromatosis arterial stenoses may show poor initial response and recurrence which is believed due to the fibrotic nature of these lesions.

For repairing blood vessels narrowed or occluded by disease, or repairing other body passageways, the length of the body passageway which requires repair, as by the insertion of a tubular prosthetic graft, may present problems if the length of the required graft cannot negotiate the curves or bends of the body passageway through which the graft is passed by the catheter. In other words, in many instances, it is necessary to support a length of tissue within a body passageway by a graft, wherein the length of the required graft exceeds the length of a graft which can be readily delivered via a catheter to the desired location within the vascular system. Some grafts do not have the requisite ability to bend so as to negotiate the curves and bends present within the vascular system, particularly prostheses or grafts which are relatively rigid and resist bending with respect to their longitudinal axes.

Accordingly, prior to the development of the present invention, there has been no expandable intraluminal vascular graft for expanding the lumen of a body passageway, which: prevents recurrence of stenoses in the body passageway; can be utilized for critical body passageways, such as the left main coronary artery of a patient's heart; prevents recoil of the body passageway wall; allows the intraluminal graft to be expanded to a variable size to prevent migration of the graft away from the desired location and prevents rupturing and/or ero-

sion of the body passageway by the expanded graft; permits tissue of an elongated section of a body passageway to be supported by an elongated graft; and provides the necessary flexibility to negotiate the bends and curves in the vascular system. Therefore, the art has sought an expandable intraluminal vascular graft which: prevents recurrence of stenoses in the body passageway; is believed to be able to be utilized in critical body passageways, such as the left main coronary artery of the heart; prevents recoil of the body passageway; can be expanded to a variable size within the body passageway to prevent migration of the graft away from the desired location and to prevent rupturing and/or erosion of the body passageway by the expanded graft; permits tissue of an elongated section of a body passageway to be supported by an elongated graft; and provides the necessary flexibility to negotiate the bends and curves in the vascular system.

SUMMARY OF THE INVENTION

In accordance with the invention, the foregoing advantages have been achieved by the present expandable intraluminal vascular graft. The present invention includes a plurality of thin-walled tubular members, each having first and second ends and a wall surface disposed between the first and second ends, the wall surface having a substantially uniform thickness and a plurality of slots formed therein, the slots being disposed substantially parallel to the longitudinal axis of each tubular member; a single connector member being disposed between adjacent tubular members to flexibly connect adjacent tubular members, the single connector member being disposed in a substantially parallel relationship with respect to the longitudinal axis of the tubular members and coplanar with each tubular member; each tubular member having a first diameter which permits intraluminal delivery of the tubular members into a body passageway having a lumen; and the tubular members having a second, expanded and deformed diameter, upon the application from the interior of the tubular members of a radially, outwardly extending force, which second diameter is variable and dependent upon the amount of force applied to the tubular members, whereby the tubular members may be expanded and deformed to expand the lumen of the body passageway.

A further feature of the present invention is that the single connector member may be a thin-walled, elongate bar member, coplanar with adjacent tubular members. An additional feature of the present invention is that a first connector member may be disposed between the second end of a first tubular

in greater detail, permits intraluminal delivery of the tubular member 71 into a body passageway 80 having a lumen 81 (FIG. 3). With reference to FIG. 1B, upon the application from the interior of the tubular member 71 of a radially, outwardly extending force, to be hereinafter described in greater detail tubular member 71 has a second, expanded diameter, d' , which second diameter d' is variable in size and dependent upon the amount of force applied to deform the tubular member 71.

Tubular member 71, may be any suitable material which is compatible with the human body and the bodily fluids (not shown) with which the vascular graft, or prosthesis, 70 may come into contact. Tubular member 71 must also be made of a material which has the requisite strength and elasticity characteristics to permit the tubular member 71 to be expanded and deformed from the configuration shown in FIG. 1A to the configuration shown illustrated in FIG. 1B and further to permit the tubular member 71 to retain its expanded and deformed configuration with the enlarged diameter d' shown in FIG. 1B and resist radial collapse. Suitable materials for the fabrication of tubular member 71 would include silver, tantalum, stainless steel, gold, titanium or any suitable plastic material having the requisite characteristics previously described.

Preferably, tubular member 71 is initially a thin-walled stainless steel tube having a uniform wall thickness, and a plurality of slots 82 are formed in the wall surface 74 of tubular member 71. As seen in FIG. 1A when tubular member 71 has the first diameter d , the slots 82 are disposed substantially parallel to the longitudinal axis of the tubular member 71. As seen in FIG. 1A, the slots 82 are preferably uniformly and circumferentially spaced from adjacent slots 82, as by connecting members 77, which connecting members 77 preferably have a length equal to the width of slots 82, as seen in FIG. 1A. Slots 82 are further uniformly spaced from adjacent slots 82 along the longitudinal axis of the tubular member 71, which spacing is preferably equal to the width of connecting members 77. Thus, the formation of slots 82 results in at least one elongate member 75 being formed between adjacent slots 82, elongate member 75 extending between the first and second ends, 72, 73 of tubular member 71, as seen in FIG. 1A.

Still with reference to FIG. 1A, each slot will have first and second ends with a connecting member 77 disposed at the first and second ends of slots 82. Preferably, the first and second ends of each slot 82 are disposed intermediate the first and second ends of adjacent slots 82 along the longitudinal axis of the tubular member 71. Thus, connecting members 77, which are disposed at the first and second ends of each slot 82, and between elongate members 75, will in turn be disposed

intermediate the first and second ends of adjacent slots 82 along the longitudinal axis of the tubular member 71. Accordingly, slots 82 are preferably uniformly and circumferentially spaced from adjacent slots, and slots 82 adjacent to one another along the longitudinal axis of tubular member 71 are in a staggered relationship with one another. Alternating slots disposed about the circumference of tubular member 71 at both the first and second ends 72, 73 of tubular member 71 will only have a length equal to approximately one-half of the length of a complete slot 82, such half-slot 82 being bounded by members 78, 79, at both the first and second ends 72, 73 of tubular member 71. Although the graft, or prosthesis, 70 of FIGS. 1A and 1B is illustrated to have a length approximately equal to the length of two slots 82, it should be apparent that the length of the graft 70 could be made longer or shorter as desired.

The foregoing described construction of graft, or prosthesis, 70 permits graft, or prosthesis, 70 to be expanded uniformly, and outwardly, in a controlled manner into the configuration shown in FIG. 1B, upon the application of a suitable force from the interior of tubular member 71, as will be hereinafter described in greater detail. The expansion of tubular member 71 into the configuration shown in FIG. 1B is further uniform along the length of tubular member 71, not only because of the uniform spacing between slots 82, as previously described, but also because the thickness of the wall surface 74, or the thickness of connecting members 77, elongate members 75, and members 78, 79, is the same uniform thickness. As illustrated in FIG. 2, the uniform thickness of elongate member 75 is shown, and the preferred cross-sectional configuration of elongate member 75, connecting member 77, and members 78, 79, is illustrated, which configuration is rectangular. It should of course be understood by those skilled in the art, that the cross-sectional configuration of the foregoing components of graft, or prosthesis, 70 could also be square, rectangular, or other cross-sectional configurations. As will be hereinafter described in greater detail, it is preferable that the outer surface 74 of graft, or prosthesis, 70, which would be in contact with the body passageway 80 FIG. 4, should be relatively smooth.

With reference to FIG. 1B, it is seen that after the graft, or prosthesis 70, has been expanded and deformed into the configuration of FIG. 1B, the slots 82 will assume a substantially hexagonal configuration when the tubular member 71 has the second, expanded diameter, d' , as shown in FIG. 1B. Such a hexagonal configuration will result when the slots 82 initially have a substantially rectangular configuration when the tubular member 71 has the first diameter, d , illustrated in FIG. 1A. It should be

is pulled away from prosthesis, or graft, 70, prior to expansion of the prosthesis, or graft, 70.

Still with reference to FIGS. 3 and 4, it should be noted that tubular member 71 of prosthesis, or graft, 70 initially has the first predetermined, collapsed diameter, d , as described in connection with FIG. 1A, in order to permit the insertion of the tubular member, 71 into the body passageway 80 as previously described. When it is desired to implant prosthesis 70 within a body passageway 80 for the purposes previously described, the prosthesis 70 is, controllably expanded and deformed to the second diameter, d' , and the second, expanded diameter, d' , is variable and determined by the internal diameter of the body passageway 80, as shown in FIG. 4, and by the amount of expansion of the inflatable portion 84 of catheter 83. Accordingly, the expanded and deformed prosthesis 70, upon deflation of angioplasty balloon 88 will not be able to migrate from the desired location within the body passageway 80, nor will the expansion of the prosthesis 70 be likely to cause a rupture of the body passageway 80. Furthermore, insofar as prosthesis, or graft, 70 is not a "spring-like" or "self-expanding member", the prosthesis is not consistently applying an outward, radial force against the interior surface of body passageway 80, in excess of that required to resist radial collapse of the body passageway 80. Thus, erosion of the interior surface, or intima, of the artery or body passageway is prevented.

When it is desired to use expandable intraluminal graft 70 to expand the lumen 81 of a body passageway 80 having an area of stenosis, the expansion of intra luminal vascular graft 70 by angioplasty balloon 88, allows controlled dilation of the stenotic area and, at the same time controlled expansion and deformation of the vascular graft 70, whereby vascular graft 70 prevents the body passageway 80 from collapsing and decreasing the size of the previously expanded lumen 81. Once again, the second, expanded diameter d' of intraluminal vascular graft 70, as shown in FIG. 4, is variable and determined by the desired expanded internal diameter of body passageway 80. Thus, the expandable intraluminal graft 70 will not migrate away from the desired location within the body passageway 80 upon deflation of angioplasty balloon 88, nor will the expansion of intraluminal graft 70 likely cause a rupture of body passageway 80, nor any erosion as previously described. Further, should an intimal flap, or fissure, be formed in body passageway 80 at the location of graft 70, graft 70 will insure that such an intimal flap will not be able to fold inwardly into body passageway 80, nor tear loose and flow through body passageway 80. In the situation of utilizing graft 70 in the manner previously described to expand the lumen

of a portion of a critical body passageway, such as the left main coronary artery, it is believed that the intimal flap will be unable to occlude the left main coronary artery of the heart and cause the death of the patient.

Because it is only necessary to inflate angioplasty balloon 88 one time in order to expand and deform graft 70, it is believed that a greater amount of endothelium, or inner layer of the intima, or inner surface of the body passageway, will be preserved, insofar as the extent of endothelial denudation during transluminal angioplasty is proportional to the balloon inflation time. Further, in theory, the amount of preserved endothelium should be large because in the expanded configuration of graft 70, potentially 80% of the endothelium is exposed through the openings or expanded slots 82 of graft 70. It is further believed that intact patches of endothelium within expanded slots 82 of graft 70 may result in a rapid, multicentric endothelialization pattern as shown by experimental studies.

With reference now to FIGS. 5 and 6, prostheses, or grafts, 70 of the type previously described in connection with FIGS. 1A and 1B are shown, and the tubular members 71 of grafts, or prostheses, 70 have a biologically inert or biologically compatible coating 90 placed upon wall surfaces 74 of tubular shaped members 71. Examples of a suitable biologically inert coating would be porous polyurethane, Teflon™, or other conventional biologically inert plastic materials. The coating 90 should be thin and highly elastic so as not to interfere with the desired expansion and deformation of prosthesis, or graft, 70. Coating 90 may be further provided with a means for anchoring 91 (FIG. 6) the tubular member 71 to the body passageway 80. Anchoring means 91 may be comprised of a plurality of radially, outwardly extending projections 92 formed on the coating 90. As seen in FIG. 6, the radially outwardly extending projections 92 could comprise a plurality of ridges 93, or other types of radially, outwardly extending projections. Further, it may be desirable to have a plurality of openings 94 formed in coating 90, as shown in FIG. 5, whereby the fluid contained in body passageway 80 can be in direct contact with the dilated, or expanded, body passageway area. Examples of biologically compatible coatings 90 would include coatings made of absorbable polymers such as those used to manufacture absorbable sutures. Such absorbable polymers include polyglycolides, polylactides, and copolymers thereof. Such absorbable polymers could also contain various types of drugs, whereby as the coating 90 is absorbed, or dissolves, the drug would be slowly released into the body passageway 80.

Turning now to FIGS. 7 and 8, an expandable

ness and a plurality of slots formed therein, the slots being disposed substantially parallel to the longitudinal axis of each tubular member;

a single connector member being disposed between adjacent tubular members to flexibly connect adjacent tubular members, the single connector member being disposed in a substantially parallel relationship with respect to the longitudinal axis of the tubular members and coplanar with each tubular member.

each tubular member having a first diameter which permits intraluminal delivery of the tubular members into a body passageway having a lumen; and the tubular members having a second, expanded and deformed diameter, upon the application from the interior of the tubular members of a radially, outwardly extending force, which second diameter is variable and dependent upon the amount of force applied to the tubular members, whereby the tubular members may be expanded and deformed to expand the lumen of the body passageway.

2. The expandable intraluminal graft of claim 1, wherein the single connector member is a thin-walled, elongate bar member, coplanar with adjacent tubular members.

3. The expandable intraluminal graft of claim 1, wherein a first connector member is disposed between the second end of a first tubular member and the first end of a second tubular member; a second connector member is disposed between the second end of the second tubular member and the first end of a third tubular member, the first and second connector members being angularly offset from one another with respect to the longitudinal axis of the tubular members.

4. An expandable prosthesis for a body passageway, comprising:

a plurality of thin-walled tubular members, each having first and second ends and a wall surface disposed between the first and second ends, the wall surface having a substantially uniform thickness and a plurality of slots formed therein, the slots being disposed substantially parallel to the longitudinal axis of each tubular member;

a single connector member being disposed between adjacent tubular members to flexibly connect adjacent tubular members, the single connector member being disposed in a substantially parallel relationship with respect to the longitudinal axis of the tubular members and coplanar with each tubular member;

each tubular member having a first diameter which permits intraluminal delivery of the tubular members into a body passageway having a lumen; and the tubular members having a second, expanded and deformed diameter, upon the application from the interior of the tubular members, of a radially, outwardly extending force, which second diameter

is variable and dependent upon the amount of force applied to the tubular member, whereby the tubular member may be expanded and deformed to expand the lumen of the body passageway.

5. The expandable prosthesis of claim 4, wherein the single connector member is a thin-walled, elongate bar member, coplanar with adjacent tubular members.

6. The expandable prosthesis of claim 4, wherein a first connector member is disposed between the second end of a first tubular member and the first end of a second tubular member; a second connector member is disposed between the second end of the second tubular member and the first end of a third tubular member, the first and second connector members being angularly offset from one another with respect to the longitudinal axis of the tubular members.

Fig. 1A




Fig. 1B




Fig. 2




Fig. 3





Fig. 4

Fig. 5







Fig. 6





European Patent
Office

EUROPEAN SEARCH REPORT

Application Number

EP 89 11 8069

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int. Cl. 5)
A	US-A-3 657 744 (ERSEN) * Abstract; column 3, lines 41-55; figures 3,4 *	1,3,4	A 61 F 2/06
A	EP-A-0 177 330 (COOK INC.)		
A	EP-A-0 282 175 (COOK INC.)		
A	EP-A-0 221 570 (PALMAZ)		
E	EP-A-0 335 341 (PALMAZ) * Abstract; figures *	1,2,4,5	
			TECHNICAL FIELDS SEARCHED (Int. Cl. 5)
			A 61 F
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 10-01-1990	Examiner STEENBAKKER J.
CATEGORY OF CITED DOCUMENTS			
X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : oral-written disclosure P : intermediate document		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons A : member of the same patent family, corresponding document	

EPO FORM 150 (01/92) (Page 1)